

K E R N O W **P R I N T** ™

053HCX14

DRY TONER

Clear Self Adhesive Film

- Permanent acrylic pressure sensitive adhesive
- Gloss Clear label stays flat
- Tear resistant waterproof face film
- Heavy weight stabilised paper liner, suitable for long print runs from production to low- to medium-speed printers
- Cost effective clarity not as good as film liner version

Compatibility Guidance:

Suitable for most thermal transfer and dry toner (laser/LED/flash fusion) print processes, both mono and colour small-volume, mid-volume & production machines.

On such machines the user must establish for themselves the optimum settings and paper path, being aware of the thickness and weight of the material.

Recommended Conditions:

Printroom	10°C - 30°C	40% - 55% RH
Usage	-40°C - 60°C	10% - 100% RH
Storage	10°C - 20°C	20% - 55% RH

Available in A4, A3 and SRA3

Thickness (54 μ /2.1mil face / 140 μ /5.5mil liner) Total Weight (229gsm)

Kernow Coatings Ltd Kernick Road Penryn, Cornwall TR10 9DQ United Kingdom

www.kernowcoatings.com	
sales@kernowcoatings.com	
T: +44 (0)1326373147	
F: +44 (0)1326376614	

Registered in England
No. 1092182
Member of the Sensitisers
Group of Companies

The information provided herein is correct to the best of our knowledge. No liability for any errors, facts or opinions is accepted. We recommend users make their own assessments to satisfy themselves as to the suitability of this product for their application. Copyright Sensitisers Group 2015