

Technical Data Sheet

Issue date: 13/05/2011 Date last modification: 22/10/2014

ROLL LABEL - RAPID JET

07978 RAPIDJET GLOSS INKJET PAPER AP904 WG62

Face Material

Gloss white coated woodfree paper.

Type Coated paper Colour and Finish White

Weight 85 g/m 2 ±10% ISO-536 Thickness 100 μ ±10% ISO 534-80

Adhesive

Acrylic permanent adhesive with good adhesion on apolar substrates (like PE and PP).

Reference AP 904

Type Acrylic permanent

Min. Appl. Temp. + 5°C

Service Temp. - 40°C/ + 100°C

Shear medium

Tack 13 N/25mm FINAT FTM9 Final Adhesion 11 N/25mm FINAT FTM2

This adhesive is approved by ISEGA (direct contact dry and moist, non fatty foodstufs) according to the German Recommendations XIV and complies with FDA 175.105.

Liner

Type One side siliconised Glassine

Colour and Finish White

Applications

Designed for photo quality printing on inkjet equipment for small or medium label volumes.

Printing Methods

Memjet, Primera and water-based inkjet technology printable.

Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

12 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- · Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.

All information is subject to change without prior notice.





