

## 053HCU14

### Clear Self Adhesive Film

- Ultra-removable pressure sensitive adhesive
- Low adhesions build & clean removability from most surfaces
- Tear resistant waterproof face film stays flat
- Heavy weight stabilised paper liner, suitable for long print runs from production to low- to medium-speed printers

#### Compatibility Guidance:

Suitable for most thermal transfer and dry toner (laser/LED/flash fusion) print processes, both mono and colour small-volume, mid-volume & production machines.

On such machines the user must establish for themselves the optimum settings and paper path, being aware of the thickness and weight of the material.

#### Recommended Conditions:

Printroom	10°C - 30°C	40% - 55% RH
Usage	-40°C - 70°C	10% - 100% RH
Storage	10°C - 20°C	20% - 55% RH

Available in A4, A3 and SRA3

Thickness (53µ/2.1mil face / 140µ/5.5mil liner) Total Weight (238gsm)

Kernow Coatings Ltd  
Kernick Road  
Penryn, Cornwall  
TR10 9DQ  
United Kingdom

[www.kernowcoatings.com](http://www.kernowcoatings.com)  
[sales@kernowcoatings.com](mailto:sales@kernowcoatings.com)  
T: +44 (0)1326373147  
F: +44 (0)1326376614

Registered in England  
No. 1092182  
A Member of the Sensitiser  
Group of Companies